

ODQF3600

Home Gas Detector



Product Overview

ODQF3600 Home Gas Detector is designed to detect flammable gas. The Micro-controller technology based gas alarm is provided with intelligent analysis and judgement function. It can detect natural gas(LNG), coal gas, LPG and smoke.

Characteristics

- Sounder and light alarm
- Power saving
- Micro-controller inspecting technology
- Built-in relay contact output and manually control

Specifications

Power Supply: AC220V/50Hz or AC120V/60Hz (ODQF3601)

Standby Power: 1.5W

Alarm Density level:

Coal gas (H ₂ dominated)	1.25% (volume ratio)	LPG	0.4% (volume ratio)
Natural Gas	1% (volume ratio)	Smoke	20% (reduced light level)

Alarm Mode: Sounder Alarm 80dB Light Alarm: Red indicator

Response Time: 20 seconds (No alarm within 1 minute after power up)

Reset Time: 20 seconds

Capacity of Output Contact Load: AC220V/0.5A DC24V/1A

Using environment: Temperature: 0°C~+50°C Related Humidity: 97%

Standard: GA-127-1996

Orena Sales and Service

Shenzhen Orena Photonics Technology Co.,Ltd

Orena Bldg, Zhong An Industrial Park, Longjing Road, Nanshan District, Shenzhen, 518055, P.R.China

Ph: 86.755.2678.7499 86.755.2678.0655 x.2719 Fax: 86.755.2678.7499

E-mail: oem@orena.com.cn

www.orena.com.cn